
STAINLESS STEEL
LAY-IN LUGS






APPLICATION

- *Lay-in design allows the conductor to be inserted from the side without removing the lug, simplifying installation and maintenance.*
- *Set screw (316 SS) secures conductor to provide a reliable mechanical and electrical connection.*
- *Engineered to terminate equipment grounding conductors to enclosures, raceways, or grounding points.*
- *Suitable for direct burial and concrete-encased installation.*
- *Type 316 SS grounding lugs offered in two sizes to accommodate the following wire ranges:*
  - *4-14 AWG*
  - *3/0–6 AWG*
- *Manufactured in stainless steel to help prevent corrosion*
- *Can be installed using ordinary hand tools and require little maintenance or repair*
- *Provided in a bright, polished finish that does not require touch up or painting*

PRODUCT DETAILS

Material:
- Lug: CF8M (316 SS)
- Grounding Screw: 316 SS

Country of Origin:
100% Made in USA



Part Number	Wire Range	Weight/ 100 (lbs.)	Dimension (in.) A	B	C	D
GL-S	4-14 AWG	62	0.88	0.44	1.35	0.20
GL-L	3/0-6 AWG	337	1.50	0.80	2.08	0.20

GIBSON STAINLESS® & SPECIALTY INC

PO BOX 847, GREENSBURG, PA 15601
PHONE: 1-800-945-4316 • FAX: 724-838-1544
WEB: GIBSONSTAINLESS.COM

© 2026 GIBSON STAINLESS & SPECIALTY, INC. - REV 9/2026