

GIBSON STAINLESS APPLICATION CROSS REFERENCE:

HANGERS, STRAPS, AND CONDUIT CLAMPS

	Rigid*		EMT		PVC-Coated		Hangers		One Hole Straps		Two Hole Straps		Two Piece Clamps		Parallel Clamps		Right Angle Clamps	
Trade Size	OD [in]	Weight per Stick ² [lbs]	OD [in]	Weight per Stick ¹ [lbs]	OD [in]	Weight per Stick ³ [lbs]	EMT	PVC	EMT	PVC	EMT	PVC	EMT	PVC	EMT	PVC	EMT	PVC
½"	0.840	8.0	0.706	2.9	0.920	8.5	Yes	Yes [^]	No	No	No	No	No	Yes			Yes	Yes
¾"	1.050	10.6	0.922	4.4	1.130	11.2	Yes	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
1"	1.315	15.3	1.163	6.4	1.395	16.4	Yes	Yes [^]	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
1 ¼"	1.660	20.2	1.510	9.5	1.740	21.7	Yes	Yes [^]	No	No	No	No	No	Yes [^]			Yes	Yes
1 ½"	1.900	25.0	1.740	11.0	1.980	26.8	Yes	Yes	No	Yes	No	No	No	Yes [^]			Yes	Yes
2"	2.375	33.4	2.197	14.0	2.455	35.8	Yes	Yes	Yes	No	Yes	No	No	Yes [^]			Yes	Yes
2 ½"	2.875	52.9	2.875	20.5	2.955	54.6	Yes	Yes [^]	Yes	No	Yes	No	Yes	Yes [^]			Yes	Yes
3"	3.500	68.6	3.500	25.0	3.580	70.8	Yes	Yes [^]	Yes	No	Yes	No	Yes	Yes [^]			Yes	Yes
3 ½"	4.000	83.5	4.000	32.5	4.080	85.1			Yes	Yes	Yes	No	Yes	Yes [^]			Yes	Yes
4"	4.500	97.6	4.500	37.0	4.580	100.9	Yes	Yes [^]	Yes	No	Yes	No	Yes	Yes [^]			Yes	Yes

*Rigid conduit dimensions provided for reference

¹Based on UL 797 minimum weight in lbs/ft multiplied by 10

²Based on UL 6A minimum weight of 100 ft of finished conduit (including 1 coupling per stick) divided by 10

³Based on nominal weight of 100 ft of finished conduit divided by 10

[^]Clamp will fit but will require 1/4" longer bolt

The above is presented as an informational tool. This guide does not constitute a guarantee of fit or performance by Gibson Stainless. Conclusions are based on comparison of standard industry dimensions and tolerances. For further information please contact Gibson Stainless.

