


# STAINLESS STEEL TB CONDUIT BODIES



## APPLICATION

- Designed to make 90° turns, change the route of conduit, and/or to make wiring pulls and connections
- Flat back design provides extra wiring capacity
- Form 8
- Offered in seven configurations: C, LB, LL, LR, T, TB, X
- Supplied complete with cover, gasket and Type 316 SS screws
- Manufactured in stainless steel to help prevent corrosion
- Can be installed using ordinary hand tools and require little maintenance or repair
- Provided in a bright, polished finish that does not require touch up or painting

## PRODUCT DETAILS

### Material:

- Body: CF8M (316 SS)
- Cover, Screws: 316 SS
- Gasket: Neoprene


**Country of Origin:** 100%  
Made in USA

### UL File Number:

QCIT.E300676  
(Standard 514A)

### Canada UL File Number:

DWTT7.E300676  
(Standard 514A)



Part Number	Size	Weight/ Each (lbs.)	Dimension (in.)				
			A	B	C	D	E
7075TB	¾ in.	3	6.67	4.31	2.88	2.00	1.50
7100TB	1 in.	3	7.57	5.00	3.23	2.31	1.75
7125TB	1-¼ in.	5	8.75	6.00	3.50	2.50	2.15
7150TB	1-½ in.	6	9.38	6.58	3.71	2.72	2.30
7200TB	2 in.	9	11.50	8.50	4.32	3.34	2.75

